
Whirlpool AUTOMATIC WASHER

Use & Care Guide



Copy Your Model and Serial Numbers Here

When you need service, or call with a question, have this information ready:

- 1. **Complete** Model and Serial Numbers (from the plate under the lid near the hinge).
- 2. Purchase date from sales slip (or date installed).

Copy this information in these spaces. Keep this book in the Laundry Information Center with your *Laundry Guide*, sales slip and warranty.

I <u>√</u> !	lodel Number
Si	er al Number
Purchas	se Installation Date

Before using your Washer

Please read this booklet to be sure your washer is installed and used properly. It will help you get the best results and longest life your washer was designed to give

You are personally responsible for making sure that your washer...

- Is installed by a gual fied installer.
- s properly installed and leveled or a floor that can support the weight.
- s connected to the right kind of outlet electric supply water supply and drain.
- is properly electrically grounded
- is used only for jobs riormally expected of home automatic washers
- is properly maintained.
- is protected from the weather.
- Is rict run by children or anyone unable to operate it properly

Remove the Consumer Buy Guide label It will be easier to remove before the washer is used

You may want to wipe out the basket with a damp cloth before using to remove dust from storing or shipping

SPECIAL INSTRUCTIONS: See the Laundry Guide for tips on detergents, other laundry aids and instructions for washing special items

See the Installation Instructions for complete information:

SAFETY FIRST

Do not permit children to operate or play with the washer.

CAUTION: Store laundry detergent and additives in a cool, dry place where children can't reach them.

SPINNING SAFETY

If the lid is opened while the basket is spinning, the basket will automatically stop in a few seconds. DO NOT ADD OR REMOVE ITEMS UNTIL THE BASKET STOPS COMPLETELY.

SPECIAL CAUTION

Flammable gases may build up in hot water pipes and heater. This can happen when hot water hasn't been used for a while (usually two weeks or more).

To prevent injury or damage, allow any gases to escape by running hot water from the faucet nearest the washer for several minutes. Don't smoke near the faucet while it is open, and turn off any open flame.

Contents

Before Using Your Washer	. 2
Loading Your Washer	. 3
MAGIC CLEAN " Lint Filter	. 3
Using Your Washer	4
Water Levels and Load Sizes	. 5
Liquid Bleach Dispenser	. 5
Important Detergent Information	6
For Rinsing Only	. 7
For Spinning Only	. 7
Cycle Operation	. 8
PERMANENT PRESS	
KNITS GENTLE	
REGULAR HEAVY	
SOAK CYCLE	10
PRE-WASH	10
If You Need Service or Assistance	10
1. Before Calling for Assistance	10
2. If You Need Assistance	11
3. If You Need Service	12
4. If You Have a Problem	



For best washing results and energy savings, sort the gundry carefully

1. Sort the Laundry into Loads.

- Group the laundry into loads that can be washed and aried together. See the Laundry Guide for information and samples of typical loads.
- Try to mix large and small items for best movement in the washer.

2. Measure Deteraent: Add to Washer Basket.

• See detergent information on page 5 and in Section IV of the Laundry Guide

3. Load the Washer.

- Load without packing so items can move freely for best cleaning and least wrinklina.
- Spread the load evenly. (Don't put all the towels on one side and a few wash cloths on the other.) An unbalanced load can cause the washer to shake durina spinnina.

4. Pour Liauid Bleach into the Dispenser.

• See page 5 and the "Laundry Aids" section of the Laundry Guide for more information.

5. Avoid Damaging Laundry.


Carefully follow package directions when using detergents, bleaches. softeners and other laundry aids. For more information, see pages 16-22 in your 'Laundry Guide'."

MAGIC CLEAN® **Lint Filter**

The lint filter is self-cleaning. It filters water used in both the wash and the rinse. When the washer drains, lint collected is flushed away.

If your washer drains into a tub. watch the drain strainer for the lint. A iinty oad can plua the tub drain and cause an overflow

Using your Washer



Start your washer after you but in detergent, the load larid any other laundry aids according to information on page 3 and page 6.

1. Set the LOAD SIZE SELECTOR.

- Select the water level that matches the size of the load. See page 5 for more information.
- To change the setting on the LOAD SIZE SELECTOR, first move it to RESET Then move it back to the setting you want

IMPORTANT For the best cleaning results with the least wrinkling, make sure the load has enough water for items to move freely.

2. Set the TEMPERATURE SELECTOR.


- Match the wash and rinse water temperatures to the type of fabrics and soils being washed (See the instructions under the washer lid and on page 14 myour Laundry Guite
- Be sure to use a cold rinse for PERMA-NENT PRESS and KNITS GENTLE Cycles

Cold water rinses save energy and help prevent wrinkles from setting into fabrics.

3. Select a Cycle and Start the Washer.

- Push the Cycle Control Knob in and turn it to the right (clockwise)
- Stop when the pointer is on the number of minutes of washing you want in the cycle you want.
- Instructions for which cycles to use for each fabric type are under the lid
- To start the washer, pull the Cycle Control Knob out. When the cycle is over, the washer will stop
- To stop the washer at any time during a cycle, push the Control Knob in. Pull it out to restart the washer
- To change a setting, push the Control Knob in to stop the washer. Then turn the Control Knob to the right (clockwise) to the setting you want. Pull the knob out to start the washer.
- Pages 8-11 show what happens in each cycle





Water Levels and Load Sizes

The LOAD SIZE SELECTOR lets you control the amount of water that fills the washer. The selector can be set at any water level between HANDWASH-ABLE and EXTRA LARGE.

WATER LEVELS		
Setting	Gallons	/Liters
HANDWASHABLE	7.8	29.5
MEDIUM	13.9	52.6
EXTRA LARGE	20.5	77.6
· Approximate fill wi	ith load.	

To change the water level setting, move the LOAD SIZE SELECTOR to RESET. Then move it to the setting you want. To save water and energy, match the water level to the load size.

For the best cleaning results, the load should move freely in the water Watch for rollover. An item (like a sock) should sink in the middle and come up later on the outside.

Be sure to read pages 11 - 13 in your *Laundry Guide* You will find more information on loading and load sizes.

IMPORTANT:

- The HANDWASHABLE setting is designed for very small loads. It uses very little water. Too big a load in this amount of water may tear some items.
- Water may splash if you use very low water levels with REG/ HEAVY. If this happens, move the LOAD SIZE SELECTOR to RESET. Then move it to a higher setting.

Liquid Bleach Dispenser

The bleach dispenser is under the lid of the washer in the front corner. It has the words, LIQUID BLEACH, on it.

- Before starting the washer, but after loading it, add the bleach.
- Use a measuring cup with a pouring spout to help avoid spilling or spattering the bleach.
- Follow the directions on the bottle for the amount to use. Never use more than 1 cup (250 mL) for a full load. Use less with lower water level settings.

Use a standard measuring cup with a pouring

spout to fill dispensers.



 Do not let any bleach run down into the washer basket. Concentrated bleach will damage any fabric.

Important Detergent Information

Detergents and soaps clean by loosening soil, and by holding it in the water so it drains away. If not enough detergent is used, soil and lint can settle back on the items in the load.

SOAP works best in soft water (0-4 grains hardness). In harder water, both the wash and rinse water should be softened. Use enough soap to make about $1\frac{1}{2}$ to 2 inches (3.8 to 5.5 cm) of suds.

DETERGENT works in hard or soft water. Package directions are usually based on soft water and

washers with normal-size tubs. **Use** more detergent...

- 1. for hard water.
- 2. for loads and water levels larger than MEDIUM.
- 3. for heavy greasy or oily soils.
- 4. if the detergent is low phosphate.
- 5. for cold-water washes.

DETERGENT SUDS. There are high, normal and low sudsing powdered detergents. If the recommended amount of detergent makes too much suds, switch to a lower sudsing brand. DO NOT REDUCE THE AMOUNT of detergent.

Use the following chart as beginning suggestions for powdered and liquid detergent amounts. See your Laundry Guide for more information (pages 14-22).

RECOMMENDED AMOUNT OF DETERGENT*- FULL TUB

	WATER HARDNESS IN GRAINS			
	0-4 Grains	4-10 Grains	10-20 Grains	
Powdered Detergents				
Low Suds	114 cups (300 mL)	1' 2 cups (350 mL)	13 4-2 cups	
			(425-475 mL)	
Normal Suds	134 cups (425 mL)	212 cups (600 mL)	3 cups (700 mL)	
High Suds	2 cups (475 mL)	3 cups (700 mL)	312 cups (825 mL)	
No phosphate	Follow package recommendations –			
Liquid Detergents	1 3 to 1 1 3 cups (80 to 325 mL), depending on the brand			
	and amount of soil. Follow package recommendations.			

- * These recommendations do not apply...
- In areas where phosphates are banned.
- In areas with laws limiting (by weight or percentage) the amount of detergent used in a wash load.

For Rinsing Only

Your washer can be set to rinse only. Use the setting for an extra rinse, or for laundry that only needs a rinse and spin.

There is a dot just after the numbers in PERMANENT PRESS, REGULAR HEAVY and KNITS GENTLE. If you push in on the Cycle Control Knob, turn the pointer to one of those dots and pull the Control Knob out, the washer will fill, agitate, drain and spin.

If you want high agitation and a high-speed spin, use the dot in REGU-LAR HEAVY. If you want low agitation and a low-speed spin, use the dot in KNITS GENTLE. Use the dot in PERMANENT PRESS if you want high agitation and a low-speed spin.




For Spinning Only

There may be times when you want to drain out all the wash water and start over. To stop the washer at any time, just push in on the Cycle Control Knob.

To set the washer so it drains and spins water out of the load, push in on the Control Knob, turn the dial to the right (clockwise) so the pointer is touching the bar just before OFF in any cycle.

The washer will drain, spin out water and stop. If you want a low-speed spin, use the bar on PERMANENT PRESS or KNITS GENTLE. All the other cycle settings have a high-speed spin.



Cycle Operation

Your washer has five cycles on the Cycle Control Dial. Each cycle is designed to match the fabric type with pre-set agitation and spin speeds. The numbers in each cycle are for the number of minutes you want the washer to agitate before it drains and fills for the rinse. You will want longer agitation times for heavily soiled loads. You choose the wash and rinse


WHAT HAPPENS IN EACH CYCLE:




- SET LOAD SIZE
- SET WATER TEMPERATURES
- PUSH IN KNOB, TURN TO CYCLE AND TIME
- PULL OUT TO START

PERMANENT PRESS CYCLE

Use for permanent press fabrics. Cooling of the wash water and low spinspeeds help prevent the setting of wrinkles.




DOWN




- SET LOAD SIZE
- SET WATER TEMPERATURES
- PUSH IN KNOB, TURN TO CYCLE AND TIME
- PULL OUT TO START

KNITS GENTLE CYCLE

Use for delicate items and washable synthetic knits such as polyester hylon acrylic. Wash hylon hose or panty hose in a net laundry bag.





- SET LOAD SIZE
- SET WATER TEMPERATURES
- PUSH IN KNOB, TURN TO CYCLE AND TIME
- PULL OUT TO START

REGULAR HEAVY CYCLE

Use for sturdy white and colorfast cottons, and for heavy work clothes. High agitation and spin speeds are preset for best cleaning results.




water temperatures you want with the **TEMPERATURE SELECTOR**.

You set the amount of water that fills the tub with the **LOAD SIZE SELECTOR**.


NOTE: You may notice that some

of the "SPIN" cycles have **SPRAY RIN-SES**. Rinse water is sprayed on the spinning load to help rinse and remove detergent residue.


If you turn to a cycle and start the washer, but change your mind push in on the Cycle Control Knob and turn to the right (clockwise) to the setting you want. Then pull it out to start




minutes after partial drain



NOTE Always use COLD RINSE WATER for Knits and Delicate items.





- SET LOAD SIZE
- SET WATER TEMPERATURE
- PUSH IN KNOB, TURN TO CYCLE AND TIME
- PULL OUT TO START

SOAK CYCLE

This by breis not for washing it spaks, agr tates ispins out the water and stops (no rinse illise attoristained velabwed grev or riedulu soilea, aunary with a detergent or pre-soak product ich orme bleach i i wanted should be added to the bycle you use after the SCAK Dyble is over





- SET LOAD SIZE
- SET WATER TEMPERATURE
- PUSH IN KNOB, TURN TO CYCLE AND TIME
- PULL OUT TO START

PRE-WASH CYCLE

use for heavily solled items that may need two washes use enough detergent for a single wash. After the washer stops, add more deteraent and select a cycle 1




If you need service or help, we suggest you follow these four steps:

1. Before calling for assistance...

Problems are sometimes caused by little things you can correct without tools

IF YOUR WASHER DOES NOT FILL:



Is the power supply cord plugged in?

Are both water faucets open?



- is a fuse blown or circuit-breaker tripped?
- Are the water supply hoses kinked?
- Is the Cycle Control Knob set and pulled out?

IF YOUR WASHER DOES NOT SPIN:


- Is the lid closed?
- Is the power supply cord plugged in?
- Is a fuse blown or circuit-breaker tripped?

IF WASHER FILLS AND DRAINS WITHOUT RUNNING:


 Make sure that the Cycle Control Knob is pointing to a number in the cycle

* Dissolve enzyme pre-soak and detergent powders to help prevent spot fading on colored items. If you use chlorine bleach, it MUST be diluted with a quart of warm water and added after the washer fills. Do not use bleach dispenser. See Laundry Guide for more information.

Before adding detergent for washing, dissolve in quart of warm water (or use liquid detergent



* Dissolve enzyme pre-soak and detergent powders to help prevent spot fading on colored items. If you use chlorine bleach, it MUST be diluted with a quart of warm water and added after the washer fills. Do not use bleach dispenser. See *Laundry Guide* for more information.



Some stains may rieed a warm or cold PRE-WASH to help prevent setting

IF YOUR WASHER STOPS DURING THE PERMANENT PRESS CYCLE.

• Remember, the washer will stop for about 172 minutes after the partial drain during the cool-down period in this cycle.

MAKE SURE THE DRAIN HOSE IS HIGHER THAN THE WATER LEVEL IN THE WASHER. IF IT ISN'T...

- The washer may seem to be draining during wash and rinse cycles.
- Water can siphon out. (See Installation Instructions.)

2. If you need assistance ...

Call the Whirlpool COOL-LINE^{*} service assistance telephone number. Dial free from:

Continental U.S. ... (800) 253-1301 Michigan (800) 632-2243 Alaska & Hawaii (800) 253-1121

and talk with one of our trained Consultants. The Consultant can instruct you in how to obtain satisfactory operation from your appliance or, if service is necessary, recommend a qualified service company in your area.

3. If you need service ...

Whiripool has a nationwide network of franchised TECH-CARE's Service Companies. TECH-CARE service technicians are trained to fulfill the product warranty and provide afterwarranty service, anywhere in the United States. To locate TECH-CARE service in your area, call our COOL-LINE service assistance telephone number (see Step 2) or look in your telephone directory Yellow Pages under:



SYMBOL OF QUALITY SERVICE

APPLIANCES—HOUSEHOLD— MAJOR—SERVICE & REPAIR

WHIRLPOOL APPLIANCES FRANC™SEC TECH CARE SERVILE

SERVICE COMPANIES XYZ SERVICE CO 123 Mag P Galagogaga ELECTRICAL APPLIANCES— MAJOR—REPAIRING & PARTS

OR FRANCHISED TECH-CARE SERVICE SERVICE COMPANIES

XYZ SERVICE CO 123 Mapie 999 9999 WASHING MACHINES, DRYERS & IRONERS—SERVICING

OR FRANCHISED TECH-CARE SERVICE

SERVICE COMPANIES

XYZ SERVICE CO
123 Maple 999-9999

4. If you have a problem ...

Call our COOL-LINE service assistance telephone number (see Step 2) and talk with one of our Consultants, or if you prefer, write to:

Mr. Guy Turner, Vice President Whirlpool Corporation Administrative Center 2000 US-33 North Benton Harbor, MI 49022

If you must call or write, please provide: model number, serial number, date of purchase, and a complete description of the problem. This information is needed in order to better respond to your request for assistance.



ESP is a registered tradernark of Whirlpoo Corporation for qualify parts Look for this symbol of quality whenever you need a replacement part for your Whirlpool appliance ESP replacement parts

wir filt right and work right, because they are made to the same exacting specifications used to build every new Whirlpool appliance.





Quality. Our way of life.

Benton Harbor, Michigan, Automatic Washers, Clothes Dryers, Freezers, Refrigerator-Freezers, Ice Makers, Dishwashers, Built-in Ovens and Surface Units, Ranges, Microwave Ovens, Compactors, Room Air Conditioners, Dehumidifiers, Central Heating and Air Conditioning Systems.

Part No. 383162 Printed in U.S.A.