


# Use and Care Manual Self-Cleaning Radiant Bake and Convection Oven

**MODELS W136, W236** 



For W236 Microwave Oven, refer to Use and Care Manual-Cat. No. MU166UA



Congratulations on your choice of a Jenn-Air wall oven.

Your Jenn-Air convection oven combines the best of two cooking methods, convection and radiant bake (conventional) baking or roasting.

The Jenn-Air convection oven is actually a conventional oven that circulates heated air within the oven. As both bake and broil heating elements cycle on and off with the thermostat, a fan keeps the heated air circulating around the food.

The constantly recirculating heated air in the convection oven strips away the layer of cooler air that surrounds food. Consequently, many foods cook more quickly. Evenly distributed heat makes multiple rack cooking possible. Convection roasted meats retain their natural flavor and juiciness with less shrinkage than radiant bake roasting.

In addition to the many exclusive benefits of convection cooking, your Jenn-Air oven is also a fine full-featured "bake and broil" oven.

You can cook your "old favorite" recipes as you have in the past. The radiant bake oven also gives you the flexibility of preparing various foods when convection cooking may not be as beneficial, as when cooking foods in covered casseroles or clay pots.

The broil element is convenient for top browning and oven broiling of foods.

The time bake feature can be used with either the convection or radiant bake oven.

Since this manual explains how you can obtain the best use of your oven, it is essential that you follow the instructions carefully. This will enable you to fully enjoy and properly maintain your Jenn-Air oven and will also assure you of achieving the finest cooking results with the foods you prepare . . . year after year.

"Complete Cooking with Jenn-Air" cookbook features outstanding recipes and cooking tips you'll enjoy using with your new Jenn-Air wall oven. A big section on oven baking contains instructions for both convection and conventional baking of each recipe. The cookbook also contains information on using a Jenn-Air grill and the various cooktop accessories. Our deluxe hardcover edition is composed of over 400 recipes with hundreds of food and "How to do it" photos (Model A905). NOTE: Use the information in this use and care as guidelines for rack positions, times, and settings when using the recipes in the cookbook.

Should you have any questions about using your Jenn-Air appliance, write to us. Be sure to provide the model number of your appliance.

Consumer Relations Department Jenn-Air Company 3035 Shadeland Avenue Indianapolis, IN 46226-0901



# Read before operating your oven

All appliances — regardless of the manufacturer — have the potential through improper or careless use to create safety problems. Therefore the following safety precautions should be observed:


- 1. Be sure your appliance is properly installed and grounded by a qualified technician.
- 2. Never use your appliance for warming or heating the room.
- 3. Children should not be left alone or unattended in area where appliance is in use. They should never be allowed to sit or stand on any part of the appliance.
- 4. Wear proper apparel. Loose-fitting or hanging garments should never be worn while using the appliance.
- 5. Do not repair or replace any part of the appliance unless specifically recommended in this manual. All other servicing should be referred to an authorized Jenn-Air Service Contractor.
- 6. Flammable materials should not be stored in an oven.
- 7. Do not use water on grease fires. Smother fire or flame or use dry chemical or foam-type extinguisher.

- 8. Use only dry potholders. Moist or damp potholders on hot surfaces may result in burns from steam. Do not let potholder touch hot heating elements. Do not use a towel or other bulky cloth.
- 9. Use care when opening oven door. Let hot air or steam escape before removing or replacing food.
- **10.** Do not heat unopened food containers. Build-up of pressure may cause container to burst and result in injury.
- 11. Keep oven vent ducts unobstructed.
- 12. Always place oven racks in desired location while oven is cool. If rack must be moved while oven is hot, do not let potholder contact hot heating element in oven.
- 13. Do not clean door gasket. The door gasket is essential for a good seal. Care should be taken not to rub, damage or move the gasket.
- 14. Do not use oven cleaners. No commercial oven cleaner or oven liner protective coating of any kind should be used in or around any part of the oven.
- 15. Clean only parts listed in this manual.
- 16. CAUTION: BEFORE SELF-CLEANING THE OVEN, REMOVE FOOD, BROILER PAN AND OTHER UTENSILS.
- Listen for fan. A fan noise should be heard during the broil and cleaning cycles. If not, call a serviceman before selfcleaning again.
- 18. DO NOT TOUCH HEATING ELEMENTS OR INTERIOR SURFACES OF OVEN. Heating elements may be hot even though they are dark in color. Interior surfaces of any oven become hot enough to cause burns. During and after use, do not touch, or let clothing or other flammable materials contact heating elements or interior surfaces of oven until they have had sufficient time to cool. Other surfaces of the appliance may become hot enough to cause burns—among these surfaces are: oven vent openings and surfaces near these openings, oven doors, windows of oven doors.



# **Oven Operation**

# **Oven Controls Panel**



# **Oven Light Switch**

 The oven light automatically comes on whenever the oven door is opened. When door is closed, push in switch to turn oven light on or off. Light cannot be turned on during the self-cleaning process.

### **Selector Knob**

 This knob controls the oven operation. To operate the oven, turn to desired setting, then turn TEMPERATURE knob to desired setting.

### The settings are:

OFF The oven will not operate when knob is on this setting. Keep knob on

this position when oven is not is use.

BAKE Use for radiant bake (conventional) baking or roasting.

TIME BAKE

Use with clock controls for automatically starting and stopping oven

when baking or roasting in the radiant bake oven.

**CONVECT** Use for convection baking or roasting.

TIME CONVECT Use with clock controls for automatically starting and stopping oven

when baking or roasting in the convection oven.

**BROIL** Use for top browning or oven broiling of foods.

CLEAN Use for self-cleaning process.

### Temperature Knob

 Use to set oven temperature. Be sure the indicator square is in line with the exact temperature desired. This knob is used with all oven operation settings noted on the SELECTOR knob.

### **Bake Indicator Light**

Indicates when oven is turned to an operating position other than the CLEAN setting.
 Light will glow until the desired temperature is reached. It will cycle on and off as this temperature is maintained during cooking.

### **Lock Indicator Light**

 Will glow after the oven door has been locked and after the oven temperature is over 550° F. Door will lock automatically and cannot be opened until oven temperature drops below 550° F.

### Clean Indicator Light

• Indicates when all controls have been properly set for the self-cleaning process. Light will remain on during the entire cleaning process.

### **Clock Controls and Minute Timer**

 Features time of day, MINUTE TIMER, and clock controls to start and stop oven automatically. (See pages 8-11.)


### **Door Lock Lever**

• Use to lock oven for self-cleaning process.

# Oven Operation Baking or Roasting

- 1. Locate oven racks on proper rack positions.
- 2. Turn TEMPERATURE knob to desired temperature.
- 3. Turn SELECTOR knob to BAKE or CONVECT setting. When the BAKE INDICATOR LIGHT cycles off, the oven is preheated to the selected temperature. Place the food in the oven. The BAKE INDICATOR LIGHT will cycle on and off throughout the baking process. *Preheat only when necessary*. Refer to baking and roasting sections as to when preheating is recommended.
- 4. After baking, turn both TEMPERATURE and SELECTOR knobs to OFF position.

### **Clock Controls**



KEY: • Dot means to push.

← Dash means to hold.

### **Clock Setting**

**IMPORTANT:** The clock is a 12 hour clock. When oven is first supplied power or power is interrupted, the display will show "00:00".

### To set time of day on clock:

- 1. Turn SET dial counterclockwise until the word TIME appears in the Display Window. Then, turn the SET dial in either direction until the correct time appears in window.
- 2. Push ENTER button.

To change time of day set on clock: Repeat above sequence.

**To check time of day when timer is in use:** Push ENTER button. Time of day will be displayed briefly, then display will return to timer function.

### Minute Timer

**IMPORTANT:** This interval timer can be used to remind you when a period, up to 99 minutes and 00 seconds, expires. It can be used independently of any other oven activity and can be set while another oven function is operating. The timer does not control the oven.

### To set MINUTE TIMER:

1. Turn SET dial clockwise until desired number of minutes and seconds appear in the Display Window.

**EXAMPLE:** Turn the dial to 5 for 5 seconds or to 5:00 for 5 minutes.

**IMPORTANT:** This is the only function where time entered is in minutes and seconds. Minutes are to the left of colon and seconds to right of colon.



### 2. Push ENTER button.

The indicator word TIMER will remain in Display Window during countdown. Countdown will have display precedence over anything else programmed, such as TIME BAKE. At end of time set, the indicator word TIMER will blink and timer will beep. Beeping will continue every 10 seconds for 15 minutes unless the CANCEL button is pushed *once*. After CANCEL button is pushed, Display will return to time of day or whatever is programmed on control panel.

To cancel MINUTE TIMER: Push CANCEL button once. Pushing CANCEL button twice will cancel all programming (time bake or self-clean).

# **Clock-Controlled Baking or Roasting**

### To set oven to start immediately and shut off automatically:

- 1. Turn SELECTOR knob to TIME BAKE or TIME CONVECT.
- 2. Turn TEMPERATURE knob to desired temperature.
- Hold in STOP TIME button until the indicator words STOP TIME appear in Display Window.
- 4. Turn SET dial to time you want food to stop cooking.

**EXAMPLE:** If time of day is one o'clock and the roast needs to cook for 3 hours, the stop time would be four o'clock.





TIME OF DAY

5. Push ENTER button to enter stop time.

The indicator word AUTO will appear in the Display Window and oven will start heating. The BAKE indicator light will glow until the desired temperature is reached.

When stop time is reached, the oven shuts off and the indicator word AUTO will begin to blink and timer will beep. Beeping will continue every 10 seconds for 15 minutes unless the CANCEL button is pushed twice.

### To set oven to start at future time and shut off automatically:

- 1. Turn SELECTOR knob to TIME BAKE or TIME CONVECT.
- 2. Turn TEMPERATURE knob to desired temperature.
- 3. Hold in START TIME button until the indicator words START TIME appear in Display Window.
- 4. Turn SET dial to time you wish food to start cooking.

**EXAMPLE:** If time of day is 11:30 and the roast needs to start cooking at one o'clock, turn dial until numbers 1:00 appear in display.





5. Push ENTER button to enter start time.

The indicator words STOP TIME will appear in Display Window as a reminder to set STOP TIME.

6. Turn SET dial to time you want food to stop cooking.

**EXAMPLE:** If start time is one o'clock and the roast needs to cook for 3 hours, the stop time would be four o'clock.





7. Push ENTER button to enter stop time.

The indicator word AUTO will blink in the Display Window. When start time is reached, the indicator word AUTO will remain in Display Window. The BAKE indicator light will glow until the desired temperature is reached.

When stop time is reached, the oven shuts off and the indicator word AUTO will begin to blink and timer will beep. Beeping will continue every 10 seconds for 15 minutes unless the CANCEL button is pushed twice.

To check START TIME <u>before</u> Cooking begins: Hold in START TIME button until the words START TIME appear in the Display Window. The start time will be displayed briefly, then Display will return to time of day.

# To change START TIME before cooking begins:

- Hold in START TIME button until the words START TIME appear in the Display Window.
- 2. Turn SET dial to desired time.
- 3. Push ENTER button *twice* to enter new start time and stop time previously programmed.

**To check STOP TIME:** Hold in STOP TIME button until the words STOP TIME appear in the Display Window. The stop time will be displayed briefly, then Display will return to on-going program.

### To change STOP TIME:

- Hold in STOP TIME button until the words STOP TIME appear in the Display Window.
- 2. Turn SET dial to desired time.
- 3. Push ENTER button to enter stop time.

To Cancel function programmed: Push CANCEL button twice to cancel function, during programmed time or after time has expired.

**NOTE:** After clock-controlled baking, turn SELECTOR and TEMPERATURE knobs to OFF position.


**NOTE:** Since food continues to cook if left in the oven, it is suggested that the clock controls be used primarily to start the oven when no one is in the kitchen. Provisions should be made to have the food removed as soon as the signal has sounded.


**NOTE:** If more than 7 seconds elapses between holding in START TIME button or STOP TIME button and turning the SET dial, the display window will automatically return to on-going program.

NOTE: If more than 1 minute elapses between turning SET dial to a new time and entering new START TIME and STOP TIME, the entire program will be cancelled and display will return to time of day clock.



# **Baking**





# **General Baking Recommendations**

- When cooking foods for the first time in your new oven, use recipe cooking times and temperatures as a guide.
- Use tested recipes from reliable sources.
- Preheat the oven only when necessary. For baked foods that rise and for richer browning, a preheated oven is better. Casseroles can be started in a cold oven. Preheating takes from 5 to 9 minutes; place food in oven after BAKE INDICATOR LIGHT cycles off.
- Arrange oven racks before turning on oven. Follow suggested rack positions on page 13 and in various baking charts.
- Allow about 1 to 1½ inches of space between the oven side walls and pans to allow proper air circulation.
- When baking foods in more than one pan, place them on opposite corners
  of the rack. Stagger pans when baking on two racks so that one pan
  does not shield another. (See above photo.)
- To conserve energy, avoid frequent or prolonged door openings. At the end of cooking, turn oven off before removing food.
- Always test for doneness (fingertip, toothpick, sides pulling away from pan). Do not rely on time or brownness as only indicators.
- Use good quality baking pans and the size recommended in the recipe.
- Dull, dark, enameled or glass pans will generally produce a brown, crisp crust. Shiny metal pans produce a light, golden crust.
- Frozen pies in shiny aluminum pans should be baked on a cookie sheet on rack 2 or be removed to a dull or glass pan.

**NOTE W236 OWNERS:** A cooling fan will cycle on and off intermittently during baking and roasting. The fan may also continue to operate after the oven is turned off.

# **Convection Baking Recommendations**


- As a general rule, when using recipes or prepared mixes developed for a radiant bake oven, set the oven temperature 25° F lower than the recipe recommended temperature. Times will be similar to or a few minutes less than recipe recommended times. The chart on page 14 compares times and temperatures of many baked foods. Use this as reference.
- For better browning, large pans such as cookie sheets or rectangular baking pans should be placed *lengthwise*, *front to back*, on the rack. This centers the food in front of the convection fan for better air circulation which gives better overall browning.
- Cookie sheets should be without sides and made of shiny aluminum. The best size to use for cookie sheets is 14" x 12" (overall size, includes handles).

### Rack Positions

The rack positions noted are generally recommended for the best browning results and most efficient cooking times. For many food items, excellent results can be achieved when *using one of several different rack positions*. Refer to baking and roasting sections for recommendations for specific foods.

#### Different Racks:

Two flat racks and one offset rack were packaged with your oven. The use of the offset rack is denoted in the list below and the charts as an "o" after the rack number.



#### Use Rack Position #1:

Large cuts of meat and large poultry, angel food cake, loaves of bread, custard pie, dessert souffle.

#### Use Rack Position #20 (offset rack on #2):

Roasting small cuts of meat, loaves of bread, angel food cake.

#### **Use Rack Position #2:**

Roasting small cuts of meat, cakes (tube, bundt or layer), frozen fruit pie, pie shell, large casseroles.

#### Use Rack Position #30 (offset rack on #3):

Most baked goods on cookie sheets, frozen convenience foods, fresh fruit pie, cream pie, layer cakes, main dish souffle.

#### **Use Rack Position #3:**


Most baked goods on cookie sheets, cakes (sheet and layer).


#### Use Rack Position #40 (offset rack on #4):

Most broiling.

#### Multiple Rack Cooking:

Two rack, use #20 and 4. Three rack, #1, 30, and 4.





# **Baking Chart**


Product and Type	Pan Size	Rack* Position	Convection Temp. (°F) Preheated***	Convection Time**	Radiant Bake Temp. (°F) Preheated	Radiant Bake Time**
CAKE						
Yellow - 2 layers	9"	2, 3o, or 3	325°	25-30	350°	30-35
White - 2 layers	9″	2, 3o, or 3	325°	22-30	350°	25-30
Chocolate - 2 layers	9"	2, 3o, or 3	325°	25-30	350°	30-35
Bundt	tube	2	325°	40-45	350°	40-53
Angel Food	tube	1, 20, or 2	350°	33-38	375°	33-38
Pound Cake	9" loaf	2	300°	50-65	325°	55-70
Cupcakes		30	325°	15-20	350°	15-25
Sheet Cake	9x13"	3	325°	28-33	350°	33-38
PIES						-
Two Crust						*
Fruit, fresh	9"	30	375°-400°	45-60	400°-425°	45-60
Fruit, frozen	9"	2	375°-400°	40-65	400°-425°	40-65
One Crust						
Custard, fresh	9"	1	325°	40-50	350°	40-50
Cream/Meringue	9"	30	375°	8-12	400°	8-12
Pie Shell	9"	2	400°-425°	8-12	425°-450°	8-12
COOKIES					astitura e d	
Chocolate Chip		3o, or 3	325°-350°	8-12	350°-375°	8-12
Peanut Butter		3o, or 3	325°-350°	8-12	350°-375°	8-12
Sugar		3o, or 3	325°-350°	8-12	350°-375°	8-12
Brownies	9x9"	30	325°	30-35	350°	33-38
BREADS, YEAST						
Loaf	loaf	1, or 2o	350°	20-25	375°	20-30
Rolls		30	375°	10-15	375°-400°	10-20
BREADS, QUICK				Activities.		
Loaf, Nut, Fruit	loaf	1, 2o, or 2	325°-350°	40-60	350°-375°	50-70
Gingerbread	9x9"	30	325°	25-30	350°	25-35
Cornbread	8x8"	30	375°-400°	15-30	400°-450°	15-30
Cornbread Muffins		30	375°	10-15	400°	10-20
Biscuits		3o, or 3	375°-400°	8-12	400°-425°	8-12
Muffins		30	375°	10-15	400°	15-20

<sup>\*</sup> An "o" after a rack number implies that the offset rack should be used.

<sup>\*\*</sup> The times given are based on specific brands of mixes or recipes tested. Actual times will depend on the ones you bake.

<sup>\*\*\*</sup> The CONVECT temperature is 25°F lower than recommended on package mix or recipe.

# Convection Baking of Frozen Convenience Foods





- Preheating the oven is not necessary.
- Follow package recommendations for oven temperature, foil covering and use
  of cookie sheets. Baking times will be similar. See chart below for some exceptions and examples.
- Center foods in the oven. If more than one food item is being baked or if foods are being baked on multiple racks, stagger foods for proper air circulation.
- Most foods are baked on rack position #3o.
- For multiple rack baking, use racks #1, 3o and 4. However, pizzas should be placed on cookie sheets and baked on rack positions #2o, 3 and 4.

# Here are a few examples of times and temperatures:

FROZEN CONVENIENCE FOODS	RACK	CONVECTION OVEN NOT PREHEATED		RADIANT BAKE PREHEATED	
	POSITION	Minutes	Temp. °F	Minutes	Temp. °F
Chicken, fried	30	35	375°	35-40	375°
Donuts, glazed	30	7	300°	6-7	300°
Fish, batter fried	3	25	375°	25-30	375°
French fries	3	18	450°	16-20	450°
Macaroni & Cheese (28 oz.)	30	47-50	375°	45-50	375°
Pot Pies	30	35-40	400°	35-40	400°
Pizza	3	17-20	400°	15-17	425°
Turkey, slices with					
gravy (TV dinner) (28 oz.)	3	55-60	375°	60	375°

# **Convection Cooking on Multiple Racks**





For best results, bake foods on one rack at a time as described in this manual. However, very good results can be obtained when baking quantities of foods on multiple racks. Quantity cooking provides both time and energy savings.

The convection oven is suggested for most multiple rack cooking, especially three rack cooking, because the circulating heated air results in more even browning than radiant. For two rack cooking, the radiant bake oven provides very good baking results especially when pans can be staggered, such as with layer cakes.

Many foods can be prepared on three racks at the same time. These are just a few examples: cookies, cupcakes, rolls, biscuits, muffins, pies, frozen convenience foods, pizzas, appetizers, and snack foods.

To obtain the best results in multiple rack cooking, follow these suggestions:

- Use temperature and times in this manual as a guide for best results.
- For two rack baking, rack positions #20 and 4 are best for most baked products but positions #2 and 4 also provide acceptable results.
- For three rack baking use positions #1, 3o and 4. One exception is pizza (see page 15).
- Since foods on positions #1 and 4 will usually be done before foods on position #30, additional cooking time will be needed for browning foods on the middle rack. An additional minute is needed for thin foods such as cookies. For foods such as biscuits, rolls, or muffins, allow 1 to 2 more minutes. Frozen pies and pizzas, which should be baked on a cookie sheet, need about 2 to 4 more minutes.
- Stagger small pans, such as layer cake pans, in the oven.
- Frozen pies in shiny aluminum pans should be placed on cookie sheets and baked on rack positions #1, 3o, and 4.
- Cookie sheets should be placed *lengthwise, front to back,* in front of the fan for more even browning.
- Oven meals are recommended for energy conservation. Use rack positions #1 and 30 or #20 and 4.



# Roasting



### **General Roasting Recommendations**


- · Preheating is not necessary.
- For open pan roasting, place meat or poultry on the slotted portion of the two-piece pan included with the oven. Do not add water to the pan. Use open pan roasting for tender cuts of meat. Less tender cuts of meat need to be cooked by moist heat in a covered pan.
- For best results, a meat thermometer is the most accurate guide to degree of doneness. The tip of the thermometer should be located in the thickest part of a roast, not touching fat, bone, or gristle. For turkeys and large poultry products, insert the tip of the thermometer into the thickest part of the inner thigh.
- Place roast fat side up to allow self basting of meat during roasting.
- Since meats continue to cook after being removed from the oven, remove roast from oven when it reaches an internal temperature about 5 degrees below the temperature desired.
- For less loss of juices and easier carving, allow about 15 minutes "standing time" after removing meat from oven.
- For best results in roasting poultry, thaw completely. Due to the structure of poultry, partially thawed poultry will cook unevenly.

# Radiant Bake Roasting Recommendations

- If preferred, tender cuts of meat can be roasted in the radiant bake oven by following the general recommendations given above. However, meats will roast more quickly in the convection oven.
- Radiant bake is best for less tender cuts of meat that require a longer, moist heat method of cooking. Follow your recipe for times and temperatures for covered meats.
- Meats cooked in cooking bags, dutch ovens, or covered roasting pans are best cooked in the radiant bake oven.
- Use meat roasting charts in standard cookbooks for recommended times and temperatures for roasting in a radiant bake oven.

**NOTE W236 OWNERS:** A cooling fan will cycle on and off intermittently during baking and roasting. The fan also continues to operate after the oven is turned off.

# **Convection Roasting Recommendations**



- Tender cuts of meat and poultry can be roasted to a rich golden brown in the convection oven. Follow general recommendations for roasting.
- Refer to convection meat roasting chart for recommended cooking temperature and time. The chart can serve as a guide to help plan meal serving time.
- Minutes per pound will vary according to the size, shape, quality, and initial temperature of meat as well as the electrical voltage in your area. Times are based on refrigerator cold meat.
- A large cut of meat will usually require fewer minutes per pound to roast than a smaller cut of meat.
- Do not use a roasting pan with high sides; use pan provided with oven.
- Do not cover meat. Allow the circulating hot air to surround the meat and seal in the juices.
- Since the breast meat on a large turkey cooks more quickly than the thigh area, place a "foil cap" over the breast area after desired brownness is reached to prevent overbrowning. (See above photo.)
- A stuffed turkey will require an extra 30 to 60 minutes depending on size.
   Stuffing should reach an internal temperature of 165°F.

# Convection Roasting: Frozen to Finish

Meats (except poultry) may be roasted frozen to finish. Follow these guidelines for the most satisfactory results.

- Use temperatures for roasting fresh meats as recommended by most cookbooks. Generally, most meats are roasted at 325°F. For best results do not use temperatures below 300°F.
- Use times for roasting fresh meats given in your favorite cookbooks as approximate guides for roasting frozen meats. Roasting times will vary due to factors such as coldness of meat, size, quality, or cut. In general, roasting times for frozen to finish in the convection oven will be approximately the same as fresh to finish in a radiant bake oven.
- The guidelines given for roasting fresh meats in the convection oven also apply to roasting frozen meats.
- Insert meat thermometer midway during the cooking process.

# Convection Roasting (Thawed Meats Only)

Variety and Cut of Meat	Approximate Weight (pounds)	Convection Oven Temperature (not preheated) °F	Internal Temperature of Meat — End of Roasting Time °F	Approximate Roasting Time (minutes per pound)	
BEEF					
Rib Roast (cutside down)	4 to 8	325°	140° (rare)	20-25	
The Hoast (edicate down)			160° (medium)	25-30	
Rib Eye Roast	4 to 6	325°	140° (rare)	20-25	
The Lyo House			160° (medium)	25-30	
Loin Tenderloin Roast	2 to 3	400°	140° (rare)	15-20	
Round Eye Round Roast	4 to 5	325°	140° (rare)	20-25	
			160° (medium)	25-30	
Top Sirloin Roast	3 to 6	325°	140° (rare)	20-25	
			160° (medium)	25-30	
Round Tip Roast	4 to 6	325°	140° (rare)	20-25	
			160° (medium)	25-30	
PORK					
Shoulder Blade Roast,	4 to 6	325°	170°	30-40	
Boneless					
Shoulder Blade Roast	4 to 6	325°	170°	25-35	
Loin Blade or Sirloin Roast	3 to 4	325°	170°	30-40	
Leg (Fresh Ham)	10 to 16	325°	170°	20-30	
Ham, Half (Fully cooked)	5 to 7	325°	140°	20-30	
Ham, Half (Cook-	5 to 7	275°	160°	30-40	
before-eating)				00.00	
Arm Picnic Shoulder	5 to 8	325°	1400	20-25	
LAMB					
Shoulder Roast, Boneless	3½ to 5	325°	160° (medium)	30-35	
			170° (well)	35-40	
Leg, Whole	5 to 7	325°	160° (medium)	25-30	
		era in la color esperante. La color esperante	170° (well)	30-35	
Leg, Shank Half	3 to 4	325°	160° (medium)	25-30	
			170° (well)	30-35	
Leg, Sirloin Half	3 to 4	325°	160° (medium)	30-35	
			170° (well)	35-40	
VEAL					
Rib Roast	3 to 5	325°	170°	35-40	
Shoulder, Boneless	4 to 6	325°	170°	35-40	
Leg, Half, Boneless	3 to 5	325°	170°	35-40	
POULTRY					
Turkey, unstuffed	8 to 12	325°	180°-185°	15-17	
Turkey, unstuffed	12 to 16	325°	180°-185°	13-15	
Turkey, unstuffed	16 to 20	325°	180°-185°	11-13	
Turkey, unstuffed	20 to 24	325°	180°-185°	9-11	
Turkey, Whole, Boneless	4 to 6	350°	170°-175°	25-35	
Turkey, Breast	3 to 8	325°	180°	25-35	
Chicken, Fryer	2½ to 3½	375°	185°	18-22	
Chicken, Roaster	4 to 6	375°	185°	15-20	
Capon, unstuffed	5 to 8	375°	180°-185°	15-20	
Cornish Game Hen	1 to 1½	375°	180°-185°	35-45	
Duck	4 to 6	350°	185°	15-20	



# **Broiling**

The broil element provides flexibility for broiling foods. If you have a Jenn-Air grill, we recommend you use the grill for most of your broiling. There are some types of foods that do require use of the oven broil element. These include foods such as stuffed lobsters, meringue pies, or other foods which require top browning.



### To Broil

- Place oven rack on the rack position suggested in the chart. Distance from broiling element depends on foods being prepared. Rack position #40 (offset rack in position #4) is usually recommended unless otherwise stated.
- Turn SELECTOR knob to BROIL setting.
- 3. Turn TEMPERATURE knob to 550°F.
- 4. Place food on roasting pan provided with oven. After top broil element is red place food in oven. Preheating takes a few minutes, or until element glows a bright cherry red.
- 5. Leave oven door open at broil stop position when broiling.

# **Broiling Tips**

- Tender cuts of meat or marinated meats are best for broiling. This includes rib and loin cuts of steak, ground beef, ham steaks, lamb chops, poultry pieces or fish. For best results, steaks should be at least 1" thick. Thinner steaks should be pan-broiled.
- Do not cover broiler grid with foil since this prevents fat drippings from draining into bottom of pan.
- Before broiling, remove excess fat from meat and score edges of fat (do not cut into meat) to prevent meat from curling. Salt after cooking.

- To prevent dry surface on fish or lean meats, brush melted butter on top.
- Foods that require turning should be turned only once during broiling. Turn
  meat with tongs to avoid piercing and loss of juices.
- Cooking times given in the chart are to be used only as a guide.
- The oven has a variable broil feature which means that the broiling temperature can be varied by selecting a lower temperature setting on the TEMPERATURE knob. Using a lower temperature setting will cause the broil element to cycle on and off. This feature can be used for foods that need to cook more slowly or need less radiant heat. If foods are broiling too fast, the control can be set at a lower temperature to reduce the cooking speed rather than moving the broiler pan to a lower rack.

**NOTE:** A fan should come on during the BROIL cycle. If it does not, the oven broil element will cycle on and off. If the fan does not operate, contact your authorized Jenn-Air Service Contractor for repair.

BROILING CHART (BROIL, 550°F, PREHEATED)					
	Rack	Approximate Minutes/Side			
FOODS	Position	1st Side	2nd Side		
BEEF Steak (1") Rare Medium	40	6	4		
Well Hamburgers (¾") Rare Medium Well	40	5 7	4 5 7		
PORK Bacon Chops (½") Chops (1") Ham Steak Sausage Patties	40 40 3 40 40	2 6 10-11 3 4	1-2 5 9-10 2 3		
Chops (1") Medium Well	40	6	6 7		
POULTRY Breast Halves (Bone-in)	3	9-10	7-10		
SEAFOOD Fish Fillets, Buttered Fish Steaks, Buttered (1")	<b>40</b>	7-9 7-9	(no turning) (no turning)		
MISCELLANEOUS Hot Dogs Toast	40 40	2			

**NOTE:** This chart is a suggested guide. The times may vary with food being cooked.



# **Oven Cleaning**

# **How the Self-Cleaning Process Works**

When the oven knobs are set to CLEAN, the oven heats to temperatures that are higher than those used for cooking. The high temperatures cause food soil to burn off and substantially disappear. While this occurs, a device in the oven vent helps to consume smoke. The oven is vented through an opening on top of the control panel.

# How to Prepare Oven Before Operating the Self-Cleaning Process

• Remove the roasting pan and any other utensils from the oven. These utensils

cannot withstand the high temperatures of the cleaning process.

 Clean spatters and spills from those areas which will not be cleaned during the selfcleaning process:

- —center front of oven and door near opening in door gasket.
- porcelain oven door liner (area outside the door gasket). (See photo at right.)
- -stainless steel oven front frame.

NOTE: DO NOT CLEAN serial plate located on the oven front.

To clean these areas, use hot water and detergent, nonabrasive cleansers or soap filled steel wool pads (rub with the brushed grain on the oven front frame to prevent scratching). Rinse thoroughly, being careful not to use an excessive amount of water that would dampen the door gasket. Soil left in these areas will be more difficult to remove after the self-cleaning process since the high heat will bake on any soil that is present. DO NOT USE COMMERCIAL OVEN CLEANERS TO CLEAN THESE AREAS.

- DO NOT ATTEMPT TO CLEAN, RUB, OR APPLY WATER TO GASKET ON OVEN DOOR. The gasket is essential for a good door seal. Rubbing or cleaning will damage the gasket and may affect the seal.
- Wipe up excess grease and food spillovers which have not baked on the bottom
  of the oven. Large accumulations of soil can cause heavy smoke or fire in
  the oven during the cleaning process.
- Although smoke or fire in the oven is a normal occurrence and there is no safety problem, there will be excessive venting of smoke and odor.


• The oven racks can be cleaned in the oven. However, the oven racks will discolor, lose shininess, and become more difficult to slide in and out if left in the oven during the cleaning process. REMOVE RACKS FROM OVEN IF THIS DISCOLORATION WILL BE OBJECTIONABLE. As a suggestion, do not leave the racks in the oven during each self-cleaning process if they do not need to be cleaned since they will discolor to a dull silver after many cleanings. Be sure to read special tips on page 27 if oven racks are cleaned during the self-cleaning process.

### **Auto Clean Feature**


This model features AUTO CLEAN to simplify cleaning an average soiled oven. To use, merely set SELECTOR and TEMPERATURE KNOBS to CLEAN, LOCK DOOR, and push ENTER button twice. The oven will clean for 2½ hours (plus cooldown time). For a heavily soiled oven or to start cleaning at a later time, refer to section below.

# Steps to Follow for Self-Cleaning Process

- 1. Turn SELECTOR knob to CLEAN.
- 2. Turn TEMPERATURE knob fully clockwise to CLEAN until it comes to a full stop. The door cannot be locked if TEMPERATURE knob is not in the CLEAN position.



- 3. Close oven door.
- 4. Move DOOR LOCK LEVER to the full right position.



5. Set clock controls to clean oven using one of the following procedures:

# To set oven to start cleaning immediately:

An automatic program of 2% hours is pre-set for an average soiled oven. For a heavily soiled oven, program can be extended up to 4 hours.

a. Push ENTER button to enter start time.

The indicator words STOP TIME will appear in Display and the time will be 2% hours later than time of day.

b. For an average soiled oven: Push ENTER button to enter stop time. The oven will beep and indicator word AUTO will appear and remain in the Display Window.

For a heavily soiled oven: Turn SET dial in clockwise direction to desired time (maximum 4 hour clean cycle). Push ENTER button to enter stop time. The oven will beep and the indicator word AUTO will appear and remain in Display Window.

# To set oven to start cleaning at a later time:

An automatic program of  $2\frac{1}{2}$  hours is pre-set for an average soiled oven. For a heavily soiled oven, program can be extended up to 4 hours.

- a. Turn SET dial to desired start time.
- b. Push ENTER button to enter START TIME. The indicator words STOP TIME will appear in Display and the time will be 2% hours later than the start time.
- c. For an average soiled oven: Push ENTER button to enter stop time. The oven will beep and the word AUTO will blink. When start time is reached, the oven will beep and the word AUTO will remain in Display Window during the cleaning cycle.

For a heavily soiled oven: Turn set dial in a clockwise direction to desired time (maximum 4 hours cleaning cycle). Push ENTER button to enter stop time. The oven will beep and the word AUTO will blink. When start time is reached, the oven will beep and the word AUTO will remain in Display Window during the cleaning process.

- **6.** The oven CLEAN INDICATOR LIGHT will glow when all steps are completed properly, except when set for a delayed start. The light goes off when stop time is reached.
- 7. The cleaning process begins immediately unless the self-cleaning process has been set for a delayed start. When the oven temperature reaches 550° F, the LOCK INDICATOR LIGHT will glow and the door cannot be opened until the temperature drops below 550° F. DO NOT TRY TO UNLOCK THE DOOR WHILE LOCK INDICATOR LIGHT IS ON. The normal cleaning process takes the time selected on the clock plus about 45 minutes for the oven to cool down before the LOCK INDICATOR LIGHT goes out and the door can be opened.

- 8. At end of time set, oven will stop automatically and not beep.
- After the LOCK INDICATOR LIGHT goes out, move the DOOR LOCK LEVER to the left. The oven door can now be opened.
- 10. Turn the SELECTOR AND TEMPERATURE knobs from CLEAN to OFF after the door is unlocked.

**IMPORTANT:** IF THE TEMPERATURE KNOB IS TURNED TO OFF BEFORE THE DOOR IS UNLOCKED, *THE DOOR WILL NOT OPEN*. Forcing the lock will damage the lock mechanism. Return TEMPERATURE knob to CLEAN, unlock the door, then turn TEMPERATURE knob OFF.

**NOTE:** A fan comes on whenever the SELECTOR knob is set on CLEAN; therefore, the fan will continue to operate at the end of the cleaning process until the SELECTOR knob is turned OFF. The fan will also start as soon as the controls are set for a delayed start of the self-cleaning process.

To check START TIME <u>before</u> cleaning begins: Hold in START TIME button until the words START <u>TIME</u> appear in the Display Window. The start time will be displayed briefly, then Display will return to time of day.

### To change START TIME before cleaning begins:

- Hold in START TIME button until the words START TIME appear in the Display Window.
- 2. Turn SET dial to time desired.
- 3. Push ENTER button to enter new start time.

The indicator words STOP TIME and a new stop time will appear in Display Window. The new stop time will be  $2\frac{1}{2}$  hours later than the new start time.

For a heavily soiled oven, the stop time will need to be changed by turning the SET dial.

4. Push ENTER button to enter new stop time.

**To check STOP TIME:** Hold in STOP TIME button until the words STOP TIME appear in the Display Window. The stop time will be displayed briefly, then Display will return to on-going program.

#### To change STOP TIME before cleaning begins:

- 1. Hold in STOP TIME button until words STOP TIME appear in the Display Window.
- 2. Turn SET dial to desired STOP TIME.

- 3. Push ENTER button to enter new stop time.
- **NOTE:** If more than 7 seconds elapse between holding in START TIME button or STOP TIME button and turning the SET dial, the display window will automatically return to on-going program.
- **NOTE:** If more than 1 minute elapses between turning SET dial to a new time and entering new START TIME *and* STOP TIME, the entire program will be cancelled and display will return to time of day clock.

#### To stop cleaning process before lock indicator light comes on:

- 1 Move the DOOR LOCK LEVER to the left.
- 2. Turn SELECTOR and TEMPERATURE knobs from CLEAN to OFF.
- 3. Push CANCEL button twice.


### To stop cleaning process after lock indicator light comes on:


- 1. Push CANCEL button twice.
- 2. Leave the TEMPERATURE and SELECTOR knobs in the CLEAN position.
- 3. Allow oven to cool until the LOCK INDICATOR LIGHT goes out. This may take up to 45 minutes, depending on how long the oven has been on.
- 4. After LOCK INDICATOR LIGHT goes off, move the DOOR LOCK LEVER to the left.
- 5. Turn SELECTOR and TEMPERATURE knobs from CLEAN to OFF.

**NOTE:** When SELECTOR knob is turned to CLEAN, a fan comes on. If this fan is not operating, the oven will go through the self-cleaning process at a reduced oven temperature and the oven will not clean effectively. If the fan does not operate, contact your Jenn-Air Authorized Service Contractor for service.

# More Information on the Self-Cleaning Process

- A slight odor may be detected, and if an oven is heavily soiled, some smoke may be visible. Some smoke and odor during the cleaning process is a normal occurrence. Since the oven is vented on top of the control panel, vapors, moisture, etc. may be seen coming from this area.
- During the cleaning process, do not be alarmed if an occasional flame is visible through the oven window. This is caused by excessive food soil that was not removed before the oven was set to clean.
- SINCE THE DOOR AND WINDOW OF THE OVEN WILL GET WARM DURING THE SELF-CLEANING PROCESS, AVOID CONTACT.
- Some types of soil may disintegrate but leave a light film or heavier deposit of ash. The amount of ash depends on the amount of soil which was in the oven. After oven has cooled, this ash may be removed with a damp sponge. If other dark deposits remain after wiping with a sponge, the time set for the length of cleaning was not enough. Increase the cleaning time for future cleanings or clean more frequently. The normal cleaning time is 2½ hours. A maximum of 4 hours may be selected if necessary.





- If racks have been left in oven during the cleaning process, they should be treated as follows. After the cleaning process is completed and the oven has cooled, buff the underside of rack edges with Scotch-Brite scour-pad or rub lightly the underside of rack edges with a coating of vegetable oil. Use a light application of oil so it does not soil the oven. As a suggestion, use fingertips to apply oil. This will make the cleaned racks slide more easily.
- To remove occasional spillovers between cleanings, use a soap-filled scouring pad or mild cleanser; rinse well.
- It is better to clean the oven regularly rather than wait until there is a heavy build-up of soil in the oven.
- During the cleaning process, the kitchen should be well ventilated to help eliminate normal odors associated with cleaning.
- Any attempt to force the self-clean DOOR LOCK LEVER to lock or unlock without electric power applied to the door or with the TEMPERATURE knob in any position other than CLEAN may result in damage to the door locking mechanism.
- DO NOT USE COMMERCIAL OVEN CLEANERS IN OR AROUND THE SELF-CLEANING OVEN AREA.
- DO NOT USE ALUMINUM FOIL OR OTHER LINERS IN THE OVEN.




# Other Hints on Caring for Your Oven

# Cleaning Other Surfaces of Your Oven

**Door and control panel trim:** The metal trim around the door and the control panel can be cleaned with any nonabrasive cleansers such as Bon-Ami or soapy water; rinse well. Be careful not to use an excessive amount of water.

Glass on the control panel front and oven door front: To clean, use any suitable glass cleaner or soapy water. To prevent moisture from getting behind the glass control panel, spray a cloth with glass cleaner then wipe the panel.

### **Oven Racks**



To remove, pull forward to the "stop" position, lift up on the front of the rack and pull out.

# **Oven Light Bulb**

Before replacing bulb, disconnect power to oven at the main fuse or circuit breaker panel. Be sure that the entire oven cavity including the light bulb is cool before attempting to remove.

To replace light bulb:

- Carefully remove the glass light lens and lens retainer by removing the two screws in the light lens retainer using a phillips screwdriver. Note: The light lens is separate from the light lens retainer. The two pieces will drop down into your hands at the same time. Do NOT remove the remaining two screws.
- 2. To obtain firm grasp on bulb, wear protective rubber gloves. Remove by turning bulb to the left. Do not touch a hot oven light bulb with a damp cloth as bulb will break. Note: If the bulb does break and you wish to remove it, be certain power supply is disconnected and wear protective gloves. You may contact your authorized Jenn-Air Service Contractor for service.
- Replace bulb with a 40 watt oven-rated appliance bulb. Bulb with brass base is recommended to prevent fusing of bulb into socket.
- 4. Place light lens inside of light lens retainer. Holding the light lens and lens retainer in place, insert the two screws into the light lens retainer and tighten.





### **Control Knobs:**

The knobs on the control panel can be removed with the controls in the OFF position. Pull each knob straight from the shaft. Wash knobs in warm soapy water or dishwasher; do not use abrasive cleansers or materials. To replace each knob, match flat part of knob opening with the spring on the shaft, returning in OFF position.

### **Oven Thermostat Knob Adjustment**


The oven thermostat knob can be adjusted if the oven temperature is too low or too high and the length of time to cook ALL foods is too long or too short. Do NOT adjust the thermostat knob if only one or two items are not baking properly.


#### To adjust the thermostat knob:

Turn the oven thermostat knob to OFF. Remove the knob and turn it to the underneath side. Hold it so that the triangle is at the top. (See Fig. 1) Loosen the two screws slightly. Holding the skirt in place, move the top screw by rotating the knob one notch, as noted by one click, in direction necessary. If notch indentation is not apparent, tighten screws until clicking is heard. There are five notches in each direction. One notch equals approximately 10°F.

**EXAMPLE:** If the oven temperature is too cool and ALL foods are requiring a longer time period to cook, the *knob should be rotated to move the top screw toward the word "HOTTER"*. (See Fig. 2)

Tighten the screws while tightly holding knob to skirt. To replace knob, match flat part of knob opening with spring on the shaft, returning to OFF position.





**IMPORTANT:** The oven thermostat knob should be adjusted one notch and then the oven should be tested. (We recommend baking 2-9" yellow layer cakes using a purchased box mix.) If the oven temperature is still too low or too high, repeat the procedure described above.

If the knob is rotated too far or in the wrong direction, rotate the knob in the opposite direction until the center of the screw is directly under the triangle, which is the starting point. Initiate the procedure again until the desired temperature is reached.

Check the following list to be sure a service call is really necessary. A quick reference of this manual, as well as reviewing additional information on items to check, may prevent an unneeded service call.

### If nothing on the oven operates:

- check for a blown circuit fuse or a tripped main circuit breaker.
- check if oven is properly connected to electric circuit in house.

### If clock and/or lights operate but oven does not heat:

- the SELECTOR and/or TEMPERATURE knobs may be set incorrectly.
- clock controls may be set for delayed start of oven.

### If the oven light does not work:

- the light bulb is loose or defective.
- oven light does not work during self-cleaning process.

### If oven will not go through self-cleaning process:

- controls may be improperly set.
- door may not be locked.
- check the "Start" and "Stop" time settings and the current time of day on the clock.

### If oven did not clean properly:

- oven may need longer cleaning time.
- · excessive spills were not removed prior to self-cleaning process.
- one or several controls may have been turned from CLEAN to another position after self-cleaning process started.

### If oven door will not unlock:

- oven may not have cooled to safe temperature after self-cleaning process.
- TEMPERATURE knob may have been switched from CLEAN position.
- electric current coming into the oven may be off.

### If foods do not broil properly:

- the SELECTOR and/or TEMPERATURE knobs may not be set properly.
- · check rack position.
- · voltage into house may be low.

### If baked food is burned or too brown on top:

- the SELECTOR knob may be in the BROIL position.
- food may be positioned incorrectly in oven.
- · oven not preheated properly.

#### If foods bake unevenly:

- the oven may be installed improperly.
- check the oven rack with a level.
- stagger pans; do not allow pans to touch each other or oven wall.
- check instructions for suggested placement of pans on oven rack.

#### If cooking results are less than expected:

- the pans being used may not be of the size or material recommended for best results.
- there may not be sufficient room around sides of the pans for proper air circulation in the oven.
- check instructions for preheating, rack position and oven temperature.

#### If baking results differ from previous oven:

oven thermostat calibration may differ between old and new ovens. The calibration
on your previous oven may have drifted to a too high or too low setting. If
you think the temperature in your new oven needs adjusting, follow the
instructions on page 29.

### If You Need Service

- call the dealer from whom your appliance was purchased or the authorized Jenn-Air Service Contractor listed in the Yellow Pages.
- your Jenn-Air Service Contractor can provide better and faster service if you
  can accurately describe problems and give model and serial number of the
  appliance. Be sure to retain proof of purchase to verify warranty status. Refer
  to WARRANTY for further information of owner's responsibilities for warranty
  service.

NOTE: Complete service and parts literature are available from any authorized Jenn-Air Parts Distributor.

All specifications subject to change by manufacturer without notice.